

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

WRINGING DEVICE FOR CLEANING ELEMENTS OF WET AND MOIST MOPSBACKGROUND OF THE INVENTION5     Field of the Invention

10     The invention relates to a wringing device for cleaning  
elements of wet and moist mops, the wringing device having a  
liquid-permeable receptacle which can be affixed to a  
container, and in which a cleaning element can be wrung out by  
the exertion of pressure, the receptacle having deformable  
wall parts and the inside width of the receptacle changing  
when the cleaning element is pressed in due to the effective  
force of pressure.

15     Description of Related Art

Such a wringing device is known from European Patent  
0 489 237. The wringing device has a liquid-permeable  
receptacle which is attached to the rim of a mop bucket and in  
which a moist mop can be wrung out by exerting pressure on it.

20     The receptacle is formed in the shape of a funnel and has  
elastically deformable wall parts arranged at a distance from  
each other. These wall parts are curved in the form of an arch  
and are attached to the mounting frame of the receptacle with

an external leg, while an inner leg is guided into in a bottom

25     part of the receptacle. The apexes of the wall parts surround  
an opening for insertion of the wet mop. To squeeze cleaning  
liquid out of the wet mop, it is introduced into the

receptacle from above and pressed downwards. The action of  
pressing the mop downwards transfers tensile forces from the

30     bottom to the inner legs of the elastic wall parts. In the  
area of the apexes, these tensile forces act as bending  
moments so that the legs are elastically deformed inwards. The

090603 "09101  
"0726" E20560

5 wall parts to be moved towards each other cause the inside width of the insertion opening to be reduced. The wall parts are pressed against the wet mop, causing the liquid to be squeezed out of it. The liquid can drain down between the wall parts into the mop bucket. When at the end of the cleaning process water is to be returned from the floor into the mop bucket by the wiping mop, the mop must be sufficiently wrung out. However, a very good wringing result can only be obtained with considerable exertion of force. In order to properly  
10 reduce the inside width of the squeeze space during squeezing, the bottom of the receptacle must be pressed strongly downwards. Only in this way is it possible to squeeze out the necessary amount of liquid, in particular from the inner area of the mop fibers. Since the squeezing pressure is not  
15 directly converted into a reduction of the squeeze space, but rather parts of the receptacle are also deformed, making it possible for the legs to move towards each other, the joints and the shoulders of the user are subjected to an undesirable load. This makes the use of the wringing device more  
20 difficult.

#### SUMMARY OF THE INVENTION

25 It is an object of the invention to specify a wringing device in which the wringing action takes place more favorably than heretofore and with less exertion of force; which has a simple structure, can be manufactured in a more cost-effective manner and is well suited for household use.

30 These and other objects of the invention are achieved in a device for cleaning elements of wet and moist mops, the wringing device having a liquid-permeable receptacle which can be affixed to a container, and in which a cleaning element can be wrung out by the exertion of pressure, the receptacle having deformable wall parts and the inside width of the  
35 receptacle changing when the cleaning element is pressed in.

due to the effective force of pressure, wherein the wall parts are in the form of spring elements with convex curvature, which can be deformed by the compression force for the purpose of enlarging the inside width.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in greater detail with reference to the following drawings wherein:

10

Fig. 1 shows a three-dimensional representation of a preferred exemplary embodiment of the wringing device,

Fig. 2 shows a top view of the exemplary embodiment according to Figure 1.

15

Handwritten: A1 with an arrow pointing to the right.

#### DETAILED DESCRIPTION OF THE INVENTION

In order to attain the objective, the wall parts are formed as spring elements with convex curvature, which can be shaped by exertion of pressure for the purpose of enlarging the inside width. In this connection, the invention is based on the knowledge that an efficient wringing result is attained in particular when the downward pressure is directly converted into a squeezing pressure and does not contribute to a deformation of parts of the receptacle, which do not result in a reduction of the squeeze space. For this purpose, the present invention provides spring elements which are convexly curved in the direction of the squeeze space in a neutral position.

20

25

During the squeezing out operation, the downward pressure does not result in a reduction but rather in an enlargement of the inside width of the squeeze space. Pressing the cleaning element in causes the spring elements to act as deformable squeezing pressure surfaces and their convex curvature is reduced as the downward pressure increases. According to the present invention, this essentially only results in an elastic

30

35

deformation of these spring elements but not in a deformation of other parts of the receptacle. This makes wringing out easier since only a slight downward pressure is necessary for a desired wringing result. The convex curvature of the spring elements which act on the mop from all sides even in the top area as the downward pressure increases, effectively converts the downward pressure into a squeezing pressure.

To remove the excess moisture from a scrub mop, a funnel-shaped receptacle has proven successful in which the spring elements form a squeeze basket tapering downwards in the shape of a tulip flower. For the wet mopping of large areas of floor coverings, a scrub mop is frequently used which can accommodate large quantities of water in absorbent strips. These absorbent strips are attached to a mop head on a handle in the form of tufts. A prerequisite for fast floor cleaning is that the strips are thoroughly rinsed by submerging them in water after each partial cleaning operation and then freeing them of excess moisture. At the end of the cleaning of a section of floor, the water containing floor dirt should be taken up as completely as possible and brought into the mop bucket by efficient wringing. The tulip-shaped, downward tapering shape of the squeeze basket can readily accommodate the large number of absorbent strips and makes it possible to wring them out with comparatively little squeezing force.

Advantageously, the receptacle has a bottom connected to a mounting frame by conical lateral surface parts, the upper end of each spring element being joined to the mounting frame and the lower end being joined to the bottom. In this manner, the distance between the bottom and the mounting frame of the receptacle is preserved during the exertion of pressure, as a result of which the downward pressure is efficiently converted into squeezing pressure, since the work of deformation is only applied to reduce the curvature of the spring elements and not

for deforming parts of the receptacle, which contribute only indirectly to the removal of liquid from the cleaning element.

The wringing device can be manufactured in a cost-effective manner as an injection molded part from a polymer material. Advantageously, the lateral surface parts of the receptacle can be formed to be sufficiently rigid and the spring elements with the desired flexibility.

In order to make it possible for the squeezed out liquid volume to drain away with as little hindrance as possible, it is advantageous if the bottom has perforations.

It is an advantage if holding lugs are provided on the mounting frame in order to affix the receptacle to the rim of a mop bucket. The holding lugs of the wringing device clutch the rim of the mop bucket so that it is always ensured that when the mop is pressed in, it is effectively supported on the rim of the bucket and does not slip. A very secure fit of the mop bucket attachment is attained if three holding lugs are provided on the wringing device. In this connection, it is an advantage if the holding lugs have a groove facing the bucket wall which engages with the top lip of the mop bucket and consequently locks the wringing device to the rim of the bucket.

With respect to manufacturing, it is advantageous if the spring elements and the lateral surface parts are arranged radially around the bottom and with interspacing, a water passage opening being formed between each spring element and lateral surface part.

It is an advantage if each spring element, seen in the direction of its extension, has a different cross-section or a different profile between the mounting frame and the bottom. As

a result, the spring elements can be designed in such a way that their pressing force varies in the vertical direction. When the cleaning element is pressed in, this also makes it possible for the liquid to be effectively pressed out of the top areas of the mop.

Preferably, an insertion funnel is located above the squeeze basket. The conical surfaces of this funnel form a guide for the strands of a mop hanging downwards, as a result of which they are bundled when they reach the insertion opening of the squeeze space.

Advantageously, a device is used for wet and moist mopping composed of a receptacle which is adapted to the scrub mop to be accommodated and the form of which is adapted to the size of the mop bucket.

Figure 1 shows a three-dimensional view of an exemplary embodiment of the wringing device according to the present invention. The wringing device is formed by a receptacle 1, having an upper insertion opening where a cleaning element, for example, a wiping mop can be inserted and can be wrung out in a squeeze basket 5.

The wringing ensues by pressure and may also include twisting and winding of the mop.

*Sub A2* Squeeze basket 5 is formed by elastically deformable wall parts 3 which are tongue-shaped and extend downwards from a mounting frame 6 of receptacle 1 with increasing tapering. Each spring element has a convex curvature and forms an inside width in the basket which becomes larger when downward pressure is exerted on the cleaning element or, expressed in other words, the curvature of the spring elements is reduced. Each spring element 3 has an upper end 8 which is preferably formed in the

shape of an arch and is molded to mounting frame 6. If an imaginary tangent is drawn at upper end 8 at the apex of a spring tongue 3, the angle enclosed between the tangent and the vertical is reduced with increasing depth in squeeze basket 5.

5 The lower end 9 of each spring element merges into a bottom 7. As can be clearly seen in Figure 2, spring elements 3 are arranged radially around bottom 7. In the embodiment of a basket-shaped squeeze chamber shown, the spring elements seen from above have the form of isosceles triangles, the upper ends

10 of which are molded to the mounting frame while their lower ends 9 merge into bottom 7. The squeeze chamber may also have a different shape, for example, a prismatic one for a flat mop head. Supports 4 are drawn between spring elements 3 which extend downwards in the form of a hollow cone and the bottom

15 ends of which also merge into bottom 7. Supports 4 form a carrier for bottom 7 and are subjected to tensile stress when downward pressure is exerted on the cleaning element. In the embodiment shown, spring elements and supports are arranged radially and with interspacing. If, in the embodiment shown, an

20 imaginary surface of revolution is formed from spring elements 3 and a surface of revolution is formed from lateral surface parts 4, these surfaces of revolution have a space between them. When the cleaning element is squeezed out, this makes it possible for the liquid squeezed out to drain away vertically

25 downwards into the mop bucket. In order to also make the drainage of liquid in the bottom easier, it has openings which are shown as holes 10 in Figure-2. In order to wring liquid out of a strand-like cleaning element bundled into a mop head, its strands hanging vertically downwards are inserted into the

30 squeeze basket which is open at the top. The squeeze basket is advantageously shaped as a tulip flower with downward tapering. Since the mop head attached to a handle is pressed downwards in the direction of bottom 7, spring elements 3 form elastically formable squeezing pressure surfaces. These opposite surfaces

35 press against the strands of the mop body when downward



pressure is exerted and squeeze out the water absorbed in them.

2ul A3

5 The exertion of pressure causes the elastically compliant  
spring elements to be pressed outwards. This causes the inside  
width of the squeeze basket to be enlarged. The downward  
pressure directed in the direction of the bottom of the bucket  
is absorbed by supports 4 which connect bottom 7 and mounting  
frame 6. In contrast to spring elements 3, which are subjected  
to a bending force when pressure is exerted on the cleaning  
10 element, supports 4 are subjected to tensile stress. During the  
pressing, their shape does not change. The wringing device can  
be affixed to the mop bucket with the aid of holding lugs 2.  
These holding lugs engage the upper rim of the top lip of a  
bucket, making it possible to lock the wringing device to the  
15 mop bucket. Three holding lugs are preferred, making it  
possible to attach the wringing device in a side area of the  
mop bucket and leave sufficient room to submerge the wiping  
mop. The embodiment of the wringing device shown in the  
drawings can be manufactured in a cost-effective manner as a  
20 plastic injection molded part. In Figure 1, the spring elements  
are shown tapering sharply to the bottom but with the same wall  
thickness. A further improvement can be obtained if the spring  
elements have a different cross-section or a different profile  
in their extension between the bottom and mounting frame. As a  
25 result, it is possible to produce opposing forces of varying  
strength of the spring elements within the basket as a function  
of their height in the basket when the cleaning element is  
pressed in. Since lateral surface parts 4 of funnel-shaped  
receptacle 1 limit the downward movement when the cleaning  
30 element is pressed in, an overexpansion of the spring elements  
is prevented. In the embodiment shown in the drawings, the  
spring elements and the lateral surface parts are arranged with  
interspacing. In Figure 2, it is clearly recognizable that a  
lateral surface part of a hollow cone of roughly equal size is  
35 arranged between each spring element as a support. The circle

segment covered in each case by the spring element and lateral surface piece may also be of varying size. Thus, it may be advantageous if the circle segment of the lateral surface parts undercuts the spring elements, as a result of which even those strands of the cleaning element that reach between the spring and lateral surface part when the mop is inserted are squeezed out.

5

096023 092101  
101260 1120560